NSN 5925-01-245-6479

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-245-6479 **Body Style:** Multipole-single actuator type **Body Length:** 3.000 inches **Body Width:** 1.484 inches **Body Height:** 2.922 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Boss Height:** 0.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 140.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 2 toggle

Actuator Function:

Trip-reset

NSN 5925-01-245-6479

Circuit Breaker - Page 2 of 2



| Actuator Position Designation: |
|---|
| At each pole |
| External Actuator Linkage Arrangement: |
| One and two linked |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 25.000 at 200 pct all locations and 80.000 at 200 pct all locations |
| Inclosure Protection Type For Which Designed: |
| General purpose |
| Trip Release Ambient Tempurature Rating: |
| 40.0 degrees celsius all locations |
| Frequency In Hertz: |
| 60.0 all locations |
| Terminal Type And Quantity: |
| 2 compression and 2 tab w/screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |