

View Online at <https://aerobasegroup.com/nsn/5925-01-247-3773>

**Pole Quantity:**

3

**Cubic Measure:**

1.000 cubic feet

**Maximum Continuous Load Current Rating Per Pole:**

1600.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1600.0 ac all locations

**Circuit Protection Type:**

Undervoltage second location

**Trip Release Method:**

Magnetic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

120.0 ac all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal and remote trip feature all locations

**Trip Release Duty Cycle:**

Intermittent all locations

**Special Features:**

For use in switchboard onboard a-class 270' u.S. Coast guard vessels

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

300.000 pounds

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0