

View Online at <https://aerobasegroup.com/nsn/5925-01-247-3773>

Pole Quantity:

3

Cubic Measure:

1.000 cubic feet

Maximum Continuous Load Current Rating Per Pole:

1600.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1600.0 ac all locations

Circuit Protection Type:

Undervoltage second location

Trip Release Method:

Magnetic all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

120.0 ac all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal and remote trip feature all locations

Trip Release Duty Cycle:

Intermittent all locations

Special Features:

For use in switchboard onboard a-class 270' u.S. Coast guard vessels

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

300.000 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0