NSN 5925-01-247-4792

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-247-4792 **Body Style:** Multipole-single actuator type **Body Length:** 6.125 inches **Body Width:** 4.125 inches **Body Height:** 3.203 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 4.750 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.187 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 200.0 amperes ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations

Reset Method: Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-247-4792

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

150.000 at 200 pct all locations and 600.000 at 200 pct all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0