NSN 5925-01-247-5949

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-247-5949

View Online at https://aerobasegroup.com/nsn/5925-01-247-5949
Body Length:
6.330 inches
Body Width:
3.000 inches
Body Height:
4.000 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.250 inches
Center To Center Distance Between Terminals Parallel To Width:
1.125 inches
Unthreaded Mounting Hole Diameter:
0.187 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
End Application:
Power panel onboard 210 ft c.G. Vessels
Boss Height:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Cubic Measure:
0.040 cubic feet
Maximum Continuous Load Current Rating Per Pole:
40.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
40.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations

NSN 5925-01-247-5949 Circuit Breaker - Page 2 of 2

Manual	
Main Contact Tripping Mechanism Type:	
Trip free	
Trip Release Duty Cycle:	
Intermittent all locations	
Trip Release Ambient Tempurature Rating	g:
50.0 degrees celsius all locations	
Frequency In Hertz:	
60.0 all locations	
Unpackaged Unit Weight:	
3.800 pounds	
Terminal Type And Quantity:	
6 compression	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	

