

View Online at <https://aerobasegroup.com/nsn/5925-01-247-9388>

Body Style:

Single pole type

Body Length:

2.150 inches

Overall Diameter:

0.750 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 terminal

Storage Type:

General purpose warehouse

Cubic Measure:

0.949 cubic inches

Maximum Continuous Load Current Rating Per Pole:

8.0 amperes ac single location and 8.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 200.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct single location and 10.000 at 200 pct single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0