## NSN 5925-01-248-9250

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-248-9250

Body Style:  Multipole-single actuator type  Bushing Length:  Between 0.332 inches and 0.380 inches  Body Length:  1.562 inches  Body Width:  1.937 inches
Bushing Length:  Between 0.332 inches and 0.380 inches  Body Length:  1.562 inches  Body Width:
Between 0.332 inches and 0.380 inches  Body Length:  1.562 inches  Body Width:
Body Length: 1.562 inches Body Width:
1.562 inches  Body Width:
Body Width:
•
1.937 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac all locations and 5.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac all locations and 50.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac all locations and 500.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

## NSN 5925-01-248-9250

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.055 at 200 pct all locations and 0.950 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and vibration resistant and shock resistant and moisture resistant and salt spray proof
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
0.330 pounds
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0