

View Online at <https://aerobasegroup.com/nsn/5925-01-250-5070>

**Body Style:**

Multipole-single actuator type

**Case Material:**

Plastic

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

2.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations and 50.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Actuator Function:**

Trip-reset

**Trip Delay Time In Seconds Per Rated Continuous Current:**

25.000 at 125 pct all locations and 450.000 at 125 pct all locations and 3.000 at 200 pct all locations and 30.000 at 200 pct all locations and 0.200 at 400 pct all locations and 4.000 at 400 pct all locations and 0.013 at 600 pct all locations and 0.100 at 600 pct all locations and 0.009 at 800 pct all locations and 0.040 at 800 pct all locations

**Special Features:**

Illuminated handle

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0