NSN 5925-01-250-5875



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-250-5875 **Body Style:** Multipole-multiple actuator type **Body Length:** 2.490 inches **Body Width:** 3.000 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.940 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.060 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.150 inches **Mounting Surface To Terminal End Distance:** 2.625 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 8 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac third location **Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac third location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac fourth location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-01-250-5875 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay first location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
135.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
4 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, three, and four linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct third location and 1.500 at 200 pct third location
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 third location
Thread Series Designator:
Unc
Terminal Type And Quantity:
8 threaded stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0