

View Online at <https://aerobasegroup.com/nsn/5925-01-251-0475>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

1.960 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.770 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct all locations and 10.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof

Special Features:

Includes illuminated handle

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0