

View Online at <https://aerobasegroup.com/nsn/5925-01-251-3454>

Body Style:

Multipole-single actuator type

Body Length:

11.000 inches

Body Width:

7.484 inches

Body Height:

4.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

9.750 inches

Center To Center Distance Between Terminals Parallel To Width:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

9.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.500 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.313 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and vibration resistant and shock resistant

Special Features:

Circuit breaker must be compatible with panelboard naec part number 625226-1

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0