NSN 5925-01-251-3454

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-251-3454

Body Style:

Multipole-single actuator type

Body Length:

11.000 inches

Body Width:

7.484 inches

Body Height:

4.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

9.750 inches

Center To Center Distance Between Terminals Parallel To Width:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

9.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.500 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.313 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-01-251-3454

Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and vibration resistant and shock resistant
Special Features:
Circuit breaker must be compatible with panelboard naec part number 625226-1
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0