

View Online at <https://aerobasegroup.com/nsn/5925-01-251-5016>

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.937 inches

Center To Center Distance Between Terminals Parallel To Width:

0.781 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.781 inches

End Application:

2 generation vortac (2gvortac)

Boss Height:

0.187 inches

Mounting Surface To Terminal End Distance:

2.469 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded stud

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overvoltage all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

50.000 all locations and 700.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Release Duty Cycle:

Continuous all locations

Special Features:

Reference data: 1cb1, fa-9996, ti-6820.2, vortac, vor/dme, vor eq., vol 8, sec 8, pg8-68

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0