

View Online at <https://aerobasegroup.com/nsn/5925-01-252-7780>

**Thread Pitch Diameters:**

+0.3507/+0.3537 inches

**Bushing Length:**

0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

1.937 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.828 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Features Provided:**

High inrush protection

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations and 10.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac all locations and 500.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Switch Location And Position Designation:**

Internal at pole two

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.055 at 200 pct all locations and 0.950 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Moisture resistant

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

0.5 ac and 0.5 dc

**Switch Voltage Rating And Type In Volts:**

120.0 ac and 50.0 dc

**Special Features:**

Two 6-32 holes included; for added mounting stability

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0