

View Online at <https://aerobasegroup.com/nsn/5925-01-254-4381>

Body Style:

Single pole type

Bushing Length:

Between 0.218 inches and 0.281 inches

Body Length:

1.094 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.673 inches and 0.805 inches

Mounting Surface To Terminal End Distance:

Between 1.281 inches and 1.378 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Ultimate Trip Time Per Pole In Seconds:

60.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

40.000 at 500 pct single location

Frequency In Hertz:

420.0 single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0