

View Online at <https://aerobasegroup.com/nsn/5925-01-258-8734>

**Thread Pitch Diameters:**

+0.3503/+0.3537 inches

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.380 inches

**Body Length:**

1.500 inches

**Body Width:**

1.875 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.844 inches and 0.906 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.594 inches and 0.656 inches

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Diameter:**

0.250 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.780 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations and 20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac all locations and 500.0 dc all locations

**Circuit Protection Type:**

Undervoltage second location

**Trip Release Method:**

Magnetic-hydraulic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

18.0 dc second location

**Trip Release Characteristic:**

Time delay first location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series/relay trip second location

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.080 at 200 pct all locations and 0.600 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed and shock resistant and vibration resistant

**Special Features:**

Relay trip coil at pole 2 rated 250 milliampere

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0