NSN 5925-01-259-1240

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-259-1240

Thread Pitch Diameters:
+0.1177/+0.1214 inches
Body Style:
Multipole-single actuator type
Body Length:
2.000 inches
Body Width:
2.265 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.530 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.660 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.130 inches
Mounting Surface To Terminal End Distance:
2.000 inches
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
6 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
2.5 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2100.0 ac all locations

NSN 5925-01-259-1240

Circuit Breaker - Page 2 of 2



Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct all locations and 1.900 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed and shock resistant and vibration resistant
Special Features:
Actuator black without markings
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
6.600 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A030a0