NSN 5925-01-259-3597



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-259-3597 **Body Style:** Single pole type **Bushing Length:** 6.5 millimeters **Body Length:** 19.8 millimeters **Body Width:** 15.8 millimeters **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 14.0 millimeters **Switch Contact Arrangement:** Single pole, double throw **Mounting Surface To Terminal End Distance:** 43.5 millimeters **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 27 **Maximum Continuous Load Current Rating Per Pole:** 100.0 milliamperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

NSN 5925-01-259-3597

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
11.000 at 200 pct single location and 60.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
73.0 degrees fahrenheit single location
Switch Terminal Type:
Quick disconnect, male
Criticality Code Justification:
Feat
Switch Current Rating And Type In Amps:
3.0 dc
Switch Voltage Rating And Type In Volts:
28.0 dc
Special Features:
Marked 1 amp for training only
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0