

View Online at <https://aerobasegroup.com/nsn/5925-01-259-3603>

Body Style:

Single pole type

Bushing Length:

6.5 millimeters

Body Length:

19.8 millimeters

Body Width:

15.8 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

14.0 millimeters

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

43.5 millimeters

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

27

Maximum Continuous Load Current Rating Per Pole:

100.0 milliamperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

11.000 at 200 pct single location and 60.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

73.0 degrees fahrenheit single location

Switch Terminal Type:

Quick disconnect, male

Criticality Code Justification:

Feat

Switch Current Rating And Type In Amps:

3.0 dc

Switch Voltage Rating And Type In Volts:

28.0 dc

Special Features:

Marked 15 amps for training only

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0