NSN 5925-01-259-3603

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-259-3603

Body Style:
Single pole type
Bushing Length:
6.5 millimeters
Body Length:
19.8 millimeters
Body Width:
15.8 millimeters
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
14.0 millimeters
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
43.5 millimeters
Pole Quantity:
1
Mounting Facility Type And Quantity:
1 threaded bushing
Thready Qty Per Inch (tpi):
27
Maximum Continuous Load Current Rating Per Pole:
100.0 milliamperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
28.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
100.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 single location
140.0 single location
140.0 single location Reset Method:
140.0 single location Reset Method: Manual
140.0 single location Reset Method: Manual Main Contact Tripping Mechanism Type:

1 push-pull

NSN 5925-01-259-3603

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
11.000 at 200 pct single location and 60.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
73.0 degrees fahrenheit single location
Switch Terminal Type:
Quick disconnect, male
Criticality Code Justification:
Feat
Switch Current Rating And Type In Amps:
3.0 dc
Switch Voltage Rating And Type In Volts:
28.0 dc
Special Features:
Marked 15 amps for training only
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0