NSN 5925-01-259-5198

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-259-5198

Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.562 inches
Body Width:
1.281 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
Thd bushing w/panel seal
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
2.0 amperes ac all locations and 2.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations and 50.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac all locations and 500.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free

NSN 5925-01-259-5198

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole two
Inclosure Protection Type For Which Designed:
Fungus resistant and hermetically sealed
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
0.5 ac and 0.5 dc
Switch Voltage Rating And Type In Volts:
120.0 ac and 50.0 dc
Frequency In Hertz:
400.0 all locations
Test Data Document:
81349-mil-c-39019 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Specification Data:
81349-mil-c-39019/4 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0