

View Online at <https://aerobasegroup.com/nsn/5925-01-259-7785>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 4.740 inches and 4.760 inches

Body Width:

4.144 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 3.540 inches and 3.560 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 1.016 inches and 1.036 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.740 inches and 2.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.016 inches and 1.036 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.210 inches and 0.230 inches

Mounting Surface To Terminal End Distance:

Between 3.540 inches and 3.560 inches

Pole Quantity:

4

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

8 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac first location 50.0 amperes ac second location 50.0 amperes ac third location

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac first location 277.0 ac second location 277.0 ac third location 120.0 dc fourth location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac first location 5000.0 ac second location 5000.0 ac third location 5000.0 dc fourth location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay first location time delay second location time delay third location instantaneous fourth location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

4 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

200.000 at 200 pct first location 200.000 at 200 pct second location 20.000 at 200 pct second location and 20.000 at 200 pct third location and 20.000 at 200 pct first location and 200.000 at 200 pct third location

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof

Frequency In Hertz:

400.0 first location 400.0 second location 400.0 third location

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0