NSN 5925-01-260-5247

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-260-5247 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** 0.740 inches **Body Width:** 0.430 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.693 inches **Fragility Factor:** Moderately rugged **End Application:** 4930-01-139-2492 **Mounting Surface To Terminal End Distance:** 1.360 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 27 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac single location and 10.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location and 24.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 60.0 ac single location and 100.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

Reset Method:

Manual

NSN 5925-01-260-5247 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
15.000 at 200 pct single location and 75.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Shock resistant and vibration resistant
Trip Release Ambient Tempurature Rating:
20.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0