

View Online at <https://aerobasegroup.com/nsn/5925-01-261-7871>

Body Style:

Single pole type

Bushing Length:

6.5 millimeters

Body Length:

19.8 millimeters

Body Width:

15.8 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

12.7 millimeters

Switch Contact Arrangement:

Double pole, double throw

Mounting Surface To Terminal End Distance:

43.5 millimeters

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

100.0 milliamperes ac single location and 100.0 milliamperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

12.0 millimeters

Thread Pitch In Millimeters:

1.25

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 60.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

150.0 degrees fahrenheit single location

Switch Terminal Type:

Quick disconnect, male

Criticality Code Justification:

Feat

Switch Current Rating And Type In Amps:

1.0 ac and 5.0 dc

Switch Voltage Rating And Type In Volts:

220.0 ac and 28.0 dc

Special Features:

Amps marked on item is for training only

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Iso m

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0