

View Online at <https://aerobasegroup.com/nsn/5925-01-261-7872>

**Body Style:**

Single pole type

**Bushing Length:**

6.5 millimeters

**Body Length:**

19.8 millimeters

**Body Width:**

15.8 millimeters

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

12.7 millimeters

**Switch Contact Arrangement:**

Double pole, double throw

**Mounting Surface To Terminal End Distance:**

43.5 millimeters

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Maximum Continuous Load Current Rating Per Pole:**

100.0 milliamperes ac single location and 100.0 milliamperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location and 1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

140.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

12.0 millimeters

**Thread Pitch In Millimeters:**

1.25

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 200 pct single location and 60.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

150.0 degrees fahrenheit single location

**Switch Terminal Type:**

Quick disconnect, male

**Criticality Code Justification:**

Feat

**Switch Current Rating And Type In Amps:**

1.0 ac and 5.0 dc

**Switch Voltage Rating And Type In Volts:**

220.0 ac and 28.0 dc

**Special Features:**

Amps marked on item is for training only

**Frequency In Hertz:**

400.0 single location

**Thread Series Designator:**

Iso m

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0