NSN 5925-01-263-3479

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-263-3479

Body Style:
Multipole-multiple actuator type
Body Length:
Between 2.480 inches and 2.500 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.940 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length
Between 2.050 inches and 2.070 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.150 inches
Mounting Surface To Terminal End Distance:
2.475 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
20.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
65.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
2000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations

NSN 5925-01-263-3479 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
3.0 millimeters
Thread Pitch In Millimeters:
0.50
Trip Delay Time In Seconds Per Rated Continuous Current:
0.700 at 200 pct all locations and 10.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Vibration resistant and moisture resistant and salt spray proof and shock resistant
Unpackaged Unit Weight:
7.400 ounces
Thread Series Designator:
lso s
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0