NSN 5925-01-263-3481

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-263-3481

Body Style:
Multipole-multiple actuator type
Body Length:
Between 2.480 inches and 2.500 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.940 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Lengt
Between 2.050 inches and 2.070 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width
0.750 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.150 inches
Mounting Surface To Terminal End Distance:
2.475 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
7.5 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
65.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations

NSN 5925-01-263-3481 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
3.0 millimeters
Thread Pitch In Millimeters:
0.50
Trip Delay Time In Seconds Per Rated Continuous Current:
0.700 at 200 pct all locations and 10.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Moisture resistant and salt spray proof and shock resistant and vibration resistant
Unpackaged Unit Weight:
7.400 ounces
Thread Series Designator:
lso s
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0