## NSN 5925-01-265-0312

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-265-0312 **Body Style:** Rectangular dimensional envelope **Overall Length:** 9.500 inches **Overall Height:** 4.000 inches **Overall Width:** 4.500 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.190 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 6 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Features Provided: Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 250.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Reset Method:** 

Trip free

**Main Contact Tripping Mechanism Type:** 

Manual

## **NSN 5925-01-265-0312** Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:	
1 toggle	
Actuator Function:	
Trip-reset	
Actuator Position Designation:	
At pole two	
Adjustable Trip Setting Current Range Per Pole In Amps:	
+1100.0/+2500.0 ac all locations	
Internal Trip Release Configuration:	
Series trip all locations	
Inclosure Protection Type For Which Designed:	
Dustproof and fungus proof	
Frequency In Hertz:	
60.0 all locations	
Terminal Type And Quantity:	
6 compression	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A030a0	