

View Online at <https://aerobasegroup.com/nsn/5925-01-265-0313>

Body Style:

Rectangular dimensional envelope

Overall Length:

12.000 inches

Overall Height:

6.812 inches

Overall Width:

9.000 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+650.0/+1300.0 ac all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Criticality Code Justification:

Feat

Special Features:

For use with new style a fuse only

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0