NSN 5925-01-265-0313

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-265-0313

Body Style:
Rectangular dimensional envelope
Overall Length:
12.000 inches
Overall Height:
6.812 inches
Overall Width:
9.000 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
125.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 all locations
125.0 all locations
125.0 all locations Manual Actuator Type And Quantity:
125.0 all locations Manual Actuator Type And Quantity: 1 toggle
125.0 all locations Manual Actuator Type And Quantity: 1 toggle Actuator Function:
125.0 all locations Manual Actuator Type And Quantity: 1 toggle Actuator Function: Trip-reset

+650.0/+1300.0 ac all locations

NSN 5925-01-265-0313

Circuit Breaker Tripper - Page 2 of 2



Trip Release Ambient Tempurature Rating: 50.0 degrees celsius all locations Criticality Code Justification: Feat Special Features: For use with new style a fuse only Frequency In Hertz: 60.0 all locations Terminal Type And Quantity: 6 compression Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A030a0