NSN 5925-01-265-0314

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-265-0314

Body Style: Rectangular dimensional envelope **Overall Length:** 12.000 inches **Overall Height:** 6.812 inches **Overall Width:** 9.000 inches **Unthreaded Mounting Hole Diameter:** 0.203 inches **Fragility Factor:** Moderately rugged **Pole Quantity:** 3 Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 4 unthreaded hole Storage Type: General purpose warehouse **Features Provided:** Adjustable trip release Maximum Continuous Load Current Rating Per Pole: 125.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations **Circuit Protection Type: Overcurrent all locations Trip Release Method:**

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+1500.0/+3000.0 ac all locations

NSN 5925-01-265-0314

Circuit Breaker Tripper - Page 2 of 2



Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

Criticality Code Justification:

Feat

Special Features:

For use with new style a fuse only

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0