

View Online at <https://aerobasegroup.com/nsn/5925-01-265-7687>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.510 inches

**Body Width:**

Between 1.437 inches and 1.563 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.660 inches and 1.960 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.719 inches and 0.781 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.046 inches and 2.078 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.719 inches and 0.781 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.109 inches and 0.171 inches

**Mounting Surface To Terminal End Distance:**

2.800 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

2.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.150 at 200 pct all locations and 1.900 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Shock resistant and vibration resistant

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

10.0 ac and 2.0 dc

**Switch Voltage Rating And Type In Volts:**

250.0 ac and 50.0 dc

**Frequency In Hertz:**

400.0 all locations

**Test Data Document:**

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

1/4"

**Terminal Type And Quantity:**

4 threaded stud

**Specification Data:**

81349-mil-c-55629/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0