NSN 5925-01-265-7692

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-265-7692

Body Style:
Single pole type
Overall Length:
3.160 inches
Body Width:
1.880 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.060 inches
Unthreaded Mounting Hole Diameter:
Between 0.195 inches and 0.225 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.406 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
2.000 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
35.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
28.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
575.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 single location
Reset Method:
Automatic
Internal Trip Release Configuration:

Series trip single location

NSN 5925-01-265-7692

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and vibration resistant and shock resistant and salt spray proof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Test Data Document:

58536-aa55571/07 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

58536-aa55571/07-001 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0