NSN 5925-01-265-7703

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-265-7703

Body Style:

Single pole type

Body Length:

3.344 inches

Body Width:

1.000 inches

Body Height:

2.312 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Boss Height:

0.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

NSN 5925-01-265-7703

Circuit Breaker - Page 2 of 2



Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Corrosion resistant

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Test Data Document:

81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 compression and 1 quick disconnect, male

Specification Data:

81348-w-c-375/13 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0