## NSN 5925-01-265-7703

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-265-7703

**Body Style:** Single pole type **Body Length:** 3.344 inches **Body Width:** 1.000 inches **Body Height:** 2.312 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 40.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

**Manual Actuator Type And Quantity:** 

1 toggle

## NSN 5925-01-265-7703

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Corrosion resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Test Data Document:
81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 compression and 1 quick disconnect, male
Specification Data:
81348-w-c-375/13 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0
A030a0