NSN 5925-01-266-0839

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-266-0839

вс	ody Style:
Sir	ngle pole type
Bo	ody Length:
Be	tween 2.480 inches and 2.500 inches
Bo	ody Width:
0.7	750 inches
Ca	ase Material:
Pla	astic
Ce	enter To Center Distance Between Terminals Parallel To Length:
1.9	940 inches
Di	stance Between Centerlines Of Mounting Facilities Parallel To Body Length
Be	etween 2.050 inches and 2.070 inches
Fra	agility Factor:
Mo	oderately rugged
Bc	oss Height:
0.1	150 inches
Mo	ounting Surface To Terminal End Distance:
2.4	475 inches
Po	ble Quantity:
1	
Ar	c Quenching Method:
Ma	agnetic blowout
Mo	ounting Facility Type And Quantity:
2 t	hreaded hole
St	orage Type:
Ge	eneral purpose warehouse
Sp	pecial Handling Feature:
Ma	agnetic
Ма	aximum Continuous Load Current Rating Per Pole:
15	.0 amperes ac single location
	perating Voltage Type And Rating Per Pole In Volts:
-	0.0 ac single location
	aximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
	00.0 ac single location
	rcuit Protection Type:
	vercurrent single location
	ip Release Method:
	agnetic single location
	ip Release Characteristic:
	me delay single location
U	timate Trip Rating Of Continuous Current Rating Per Pole In Percent: 5.0 single location

NSN 5925-01-266-0839

Circuit Breaker - Page 2 of 2



Reset Met	hod:
Manual	
Main Con	tact Tripping Mechanism Type:
Trip free	
Manual A	ctuator Type And Quantity:
1 toggle	
Actuator I	Function:
Trip-reset	
Actuator I	Position Designation:
At pole on	e
Internal T	rip Release Configuration:
Series trip	single location
Thread Si	ze:
3.0 millime	oters
Thread Pi	tch In Millimeters:
0.50	
Trip Delay	Time In Seconds Per Rated Continuous Current:
2.000 at 2	200 pct single location and 22.000 at 200 pct single location
Inclosure	Protection Type For Which Designed:
Moisture re	esistant and salt water resistant and shock resistant and vibration resistant
Frequenc	y In Hertz:
50.0 single	e location or 60.0 single location
Unpackag	ed Unit Weight:
3.700 oun	ces
Thread Se	eries Designator:
lso m	
Terminal ⁻	Type And Quantity:
2 threaded	l stud
Shelf Life	:
N/a	
Unit Of M	easure:
Demilitari	zation:
No	
Fiig:	
A030a0	