

View Online at <https://aerobasegroup.com/nsn/5925-01-266-0843>

Body Style:

Single pole type

Body Length:

Between 2.480 inches and 2.500 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.050 inches and 2.070 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.475 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

3.0 millimeters

Thread Pitch In Millimeters:

0.50

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 22.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Frequency In Hertz:

50.0 single location or 60.0 single location

Unpackaged Unit Weight:

3.700 ounces

Thread Series Designator:

Iso m

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0