NSN 5925-01-266-7141

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-266-7141

## **Body Style:**

Multipole-single actuator type

#### **Bushing Length:**

0.380 inches

# **Body Length:**

1.562 inches

## Body Width:

1.937 inches

#### **Case Material:**

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

#### 0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

## Fragility Factor:

Moderately rugged

## Mounting Surface To Terminal End Distance:

1.780 inches

## **Pole Quantity:**

3

## Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

## Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Magnetic all locations

## **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# NSN 5925-01-266-7141

Circuit Breaker - Page 2 of 2

| Reset Method:              |   |
|----------------------------|---|
| Manual                     |   |
| Main Contact Tripping      | Aechanism Type:                         |
| Trip free                  |   |
| Manual Actuator Type       | And Quantity:                           |
| 1 toggle                   |   |
| Actuator Function:         |   |
| Trip-reset                 |   |
| Actuator Position Desig    | ination:                                |
| Between pole one and tw    | 0                                       |
| Internal Trip Release Co   | onfiguration:                           |
| Series trip all locations  |   |
| Thread Size:               |   |
| 0.375 inches               |   |
| Trip Delay Time In Seco    | onds Per Rated Continuous Current:      |
| 0.500 at 200 pct all locat | ions and 9.000 at 200 pct all locations |
| Inclosure Protection Ty    | pe For Which Designed:                  |
| Hermetically sealed and    | vibrationproof and shockproof           |
| Frequency In Hertz:        |   |
| 400.0 all locations        |   |
| Unpackaged Unit Weigl      | nt:                                     |
| 5.400 ounces               |   |
| Thread Series Designat     | or:                                     |
| Unef                       |   |
| Terminal Type And Qua      | ntity:                                  |
| 6 wire hook                |   |
| Shelf Life:                |   |
| N/a                        |   |
| Unit Of Measure:           |   |
|                            |   |
| Demilitarization:          |   |
| No                         |   |
| Fiig:                      |   |
| A030a0                     |   |

