

View Online at <https://aerobasegroup.com/nsn/5925-01-267-1049>

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

2 terminal

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

60.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Inclosure Protection Type For Which Designed:**

Dustproof

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 clip

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0