

View Online at <https://aerobasegroup.com/nsn/5925-01-268-3172>

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

1.937 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct all locations and 9.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed and vibrationproof and shockproof

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

5.400 ounces

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0