

View Online at <https://aerobasegroup.com/nsn/5925-01-268-3175>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.625 inches

Body Length:

2.265 inches

Body Width:

2.000 inches

Center To Center Distance Between Terminals Parallel To Width:

1.530 inches

Mounting Surface To Terminal End Distance:

2.232 inches

Pole Quantity:

3

Maximum Continuous Load Current Rating Per Pole:

15.00 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Trip Release Method:

Magnetic single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 200 pct single location and 160.000 at 200 pct single location

Frequency In Hertz:

400.0 single location

Test Data Document:

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349mil-c-55629/22 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0