

View Online at <https://aerobasegroup.com/nsn/5925-01-268-3175>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

0.625 inches

**Body Length:**

2.265 inches

**Body Width:**

2.000 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.530 inches

**Mounting Surface To Terminal End Distance:**

2.232 inches

**Pole Quantity:**

3

**Maximum Continuous Load Current Rating Per Pole:**

15.00 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

**Trip Release Method:**

Magnetic single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Trip Delay Time In Seconds Per Rated Continuous Current:**

20.000 at 200 pct single location and 160.000 at 200 pct single location

**Frequency In Hertz:**

400.0 single location

**Test Data Document:**

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349mil-c-55629/22 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0