

NSN 5925-01-269-2453 Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-269-2453 **Body Style:** Multipole-multiple actuator type **Body Length:** 2.500 inches **Body Width:** 1.500 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.938 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches

Fragility Factor:
Moderately rugged

Boss Height: 0.140 inches

Mounting Surface To Terminal End Distance:

2.471 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

12.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-01-269-2453 Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct all locations and 20.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0