NSN 5925-01-270-2119

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-270-2119

Body Style:

Multipole-single actuator type

Body Length:

8.000 inches

Body Width:

4.500 inches

Body Height:

3.660 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

7.130 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.130 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Boss Height:

0.188 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

200.0 amperes ac all locations and 200.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+1125.0/+2250.0 ac all locations and +1125.0/+2250.0 dc all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

Special Features:

Unit includes a shunt trip accessory used to trip the breaker from a remote location; rated at 240 volts, 400 hertz

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0