

View Online at <https://aerobasegroup.com/nsn/5925-01-274-1288>

**Body Style:**

Multipole-single actuator type

**Mounting Slot Width:**

0.563 inches

**Body Length:**

4.250 inches

**Body Width:**

3.000 inches

**Body Height:**

2.625 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

1.000 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.188 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

3 slot and 3 terminal

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

277.0 ac all locations and 480.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

14000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Trip Delay Time In Seconds Per Rated Continuous Current:**

9.000 at 200 pct all locations and 70.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and general purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

3 compression and 3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0