

View Online at <https://aerobasegroup.com/nsn/5925-01-274-1289>

**Body Style:**

Single pole type

**Body Length:**

3.000 inches

**Body Width:**

0.187 inches

**Body Height:**

2.375 inches

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**End Application:**

4920-01-082-1095

**Boss Height:**

1.000 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 terminal

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

65000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Instantaneous single location and time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

20.000 at 200 pct single location and 90.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

1 clip and 1 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0