NSN 5925-01-274-1290

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-274-1290

Body Style:

- Single pole type
- **Bushing Length:**
- 0.250 inches

Body Length:

- 1.781 inches
- **Body Width:**
- 0.656 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.341 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

1.669 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

250.0 milliamperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-274-1290

Circuit Breaker - Page 2 of 2



Mar	nual Actuator Type And Quantity:
1 թւ	ush-pull
Act	uator Function:
Trip	-reset
Act	uator Position Designation:
At p	oole one
Aux	ciliary Switch Function And Quantity:
1 ala	arm
Inte	rnal Trip Release Configuration:
Seri	ies trip single location
Thre	ead Size:
0.46	69 inches
Swi	tch Location And Position Designation:
Inte	rnal at pole one
Incl	osure Protection Type For Which Designed:
Dus	tproof and corrosion resistant and fungus resistant and sand resistant
Swi	tch Terminal Type:
Tab	, solder lug
Swi	tch Current Rating And Type In Amps:
7.0	dc
Swi	tch Voltage Rating And Type In Volts:
28.0) dc
Unp	backaged Unit Weight:
2.00	00 ounces
Thre	ead Series Designator:
Uns	3
Teri	minal Type And Quantity:
2 tal	b w/screw
She	elf Life:
N/a	
Unit	t Of Measure:
Den	nilitarization:
No	
Fiig	r.
A03	30a0