

View Online at <https://aerobasegroup.com/nsn/5925-01-274-6529>

Body Style:

Multipole-single actuator type

Mounting Slot Width:

0.563 inches

Body Length:

4.250 inches

Body Width:

3.000 inches

Body Height:

2.625 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.188 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

3 slot and 3 terminal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac all locations and 480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

9.000 at 200 pct all locations and 70.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and general purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

3 compression and 3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0