

View Online at <https://aerobasegroup.com/nsn/5925-01-277-1980>

**Bushing Length:**

0.380 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.875 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Maximum Continuous Load Current Rating Per Pole:**

500.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 50.0 dc single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.400 at 125 pct single location and 4.000 at 125 pct single location and 0.060 at 200 pct single location and 0.600 at 200 pct single location and 0.010 at 400 pct single location and 0.200 at 400 pct single location and 0.005 at 800 pct single location and 0.035 at 800 pct single location

**Frequency In Hertz:**

60.0 single location or 400.0 single location

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0