

View Online at <https://aerobasegroup.com/nsn/5925-01-277-4374>

Body Style:

Multipole-single actuator type

Body Length:

Between 1.995 inches and 2.005 inches

Body Width:

Between 2.165 inches and 2.175 inches

Body Height:

Between 1.765 inches and 1.770 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

Between 0.620 inches and 0.630 inches

Boss Height:

Between 0.120 inches and 0.130 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 clip

Storage Type:

General purpose warehouse

Features Provided:

High inrush protection

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

1.150 at 200 pct all locations and 7.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Unpackaged Unit Weight:

3.900 ounces

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0